


### OTHER SPECIFICATIONS:

(1) POLARIZER:	
(2) VIEWING DIRECTION:	
(3) PIN:	
PIN LENGTH:	
(4) OPERATING VOLTAGE:	
(5) DRIVING SCHEME: DIRECT	
V(on):	V(off):
(6) TEMPERATURE RANGE:	
OPERATING:	
STORAGE:	
(7) GRADE:	
(8) NOTES:	

### PIN-OUT CONFIGURATION OF EXCELIX 4500M3

PIN NO.	1	2	3	4	5	6	7	8	9	10
COM1	-	-	-	B1	B2	B3	B4	-	-	-
COM2	-	-	-	C1	C2	C3	C4	-	-	-
COM3	-	-	-	DP1	DP2	DP3	-	COM3	-	-

PIN NO.	11	12	13	14	15	16	17	18	19	20
COM1	COM1	A4	F4	A3	F3	A2	F2	A1	F1	-
COM2	-	G4	E4	G3	E3	G2	E2	G1	E1	COM2
COM3	-	D4	-	D3	-	D2	-	D1	-	-

 <b>EXCEL TECHNOLOGY INT'L CORP.</b> 5-4 Stryker Lane, Belle Mead, NJ 08502 TEL: (908) 874-4747 FAX: (908) 874-3278			
MODEL NO.	UNIT	SCALE	DATE
4500M3	IN		04/24/92
VERSION	DESIGN	CHECKED	APPROVAL
3	SNC		