



OTHER SPECIFICATIONS:

| |
|--|
| (1) POLARIZER: Reflective |
| (2) VIEWING DIRECTION: 6 O'Clock |
| (3) PIN: DIL PIN LENGTH: 0.25 |
| (4) OPERATING VOLTAGE: 5V |
| (5) DRIVING SCHEME: Direct V(on): V(off): |
| (6) TEMPERATURE RANGE: OPERATING: -30° to 85° STORAGE: -30° to 85° |
| (7) GRADE: Commercial |
| (8) NOTES: |

PIN-OUT CONFIGURATION OF EXCELIX 4700

| | | | | | | | | | | |
|---------|----|----|----|----|----|----|----|----|----|----|
| PIN NO. | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| SEG | BP | NC | NC | NC | E1 | D1 | C1 | DP | E2 | D2 |
| PIN NO. | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| SEG | C2 | DP | E3 | D3 | C3 | DP | E4 | D4 | C4 | B4 |
| PIN NO. | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 |
| SEG | A4 | F4 | G4 | B3 | A3 | F3 | G3 | K1 | B2 | A2 |
| PIN NO. | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 |
| SEG | F2 | G2 | NC | B1 | A1 | F1 | G1 | NC | NC | NC |

| | | | |
|---|--------|---------|----------|
| EXCEL TECHNOLOGY INT'L CORP. 5-4 Stryker Lane, Belle Mead, NJ 08502 Tel: (908) 874-4747, Fax: (908) 874-3278 | | | |
| MODEL NO. | UNIT | SCALE | DATE |
| 4700 | in | | |
| VERSION | DESIGN | CHECKED | APPROVAL |
| 2 | | | |